

# EPDM-Tape



### Technical characteristics

Building material class DIN 4102	B2 (normal flammable)
Fire classification EN 13501-1	Class E
Water vapour resistance factor	32'000 µ
Temperature resistance	-30°C up to +80°C
UV resistance	24 months
Elongation	250%
Storage temperature	+5°C up to +25°C
Storage time	2 years

### Application


Sealing tape to protect the timber batten against humidity

### Material

Elastomer sheet made of black EPDM rubber

### Features and Benefits

- High resistance to mechanical damage
- Excellent movement capability in both transverse and longitudinal direction
- High ageing resistance
- Solvent free



## Sealing tape EPDM

Product code	PU	Wide tape (mm)	Thickness tape (mm)	Roll length (m)	
EPDM-TAPE-0,75×60×25000	1	60	0.75	25	1122506
EPDM-TAPE-0,75×80×25000		80			1193862
EPDM-TAPE-0,75×100×25000		100			1122504
EPDM-TAPE-0,75×120×25000		120			1288745

## Sealing tape EPDM self adhesive on one side

Product code	PU	Wide tape (mm)	Thickness tape (mm)	Roll length (m)	
EPDM-TAPE-ADHESIVE-0,75×60×25000	1	60	0.75	25	1122507
EPDM-TAPE-ADHESIVE-0,75×100×25000		100			1122508
EPDM-TAPE-ADHESIVE-0,75×120×25000		120			1329007